

Shib2IdPMobileLogin

A Shibboleth autentikációs képernyője tetszőlegesen testre szabható. A fájl a `war/idp.war`-ban található. Módosításhoz ki kell csomagolni, módosítani a `login.jsp`-t majd visszacsomagolni.

Lévén egyre többen használunk webes szolgáltatásokat mobilon keresztül, jó szolgálatot tehet, ha a Shibboleth belépő oldala is optimalizált a kis kijelzőkre és nem kell a nagy fehérségben matatnunk, hogy rámutassunk a felhasználónév mezőre...

Az alábbi, Shibboleth 2.3-hoz készült, módosított `login.jsp` a jQuery mobile környezetét használja a megjelenítéshez, így a legtöbb mobilon ugyanúgy kell megjelennie. A kód természetesen tovább szabható, formálható. Fontos, hogy javascript nélkül is működik, csak nem lesz szép.

```
<%@ taglib uri="urn:mace:shibboleth:2.0:idp:ui" prefix="idpui" %>
<%

String ua=request.getHeader("User-Agent").toLowerCase();
if(ua.matches(".*(android|avantgo|blackberry|blazer|compal|elaine|fennec|hiptop|iemoobile|ip(ho
ne|od)|iris|kindle|lge |maemo|midp|mmp|opera m(ob|in)i|palm(
os)?|phone|(ixi|re)\\/|plucker|pocket|psp|symbian|treo|up\\.(browser|link)|vodafone|wap|windo
ws (ce|phone)|xda|xiino).*")||ua.substring(0,4).matches("1207|6310|6590|3gso|4thp|50[1-
6]i|770s|802s|a wa|abac|ac(er|oo|s\\-
)|ai(ko|rn)|al(av|ca|co)|amoi|an(ex|ny|yw)|aptu|ar(ch|go)|as(te|us)|attw|au(di|\\-m|r |s
)|avan|be(ck|ll|nq)|bi(lb|rd)|bl(ac|az)|br(e|v)w|bumb|bw\\-(n|u)|c55\\\/|capi|ccwa|cdm\\-
|cell|chtm|cldc|cmd\\-|co(mp|nd)|craw|da(it|ll|ng)|dbte|dc\\-
s|devi|dica|dmob|do(c|p)o|ds(12|\\-d)|el(49|ai)|em(l2|ul)|er(ic|k0)|esl8|ez([4-
7]0|os|wa|ze)|fetc|fly(\\-|_)|g1 u|g560|gene|gf\\-5|g\\-
mo|go(\\-w|od)|gr(ad|un)|haie|hcit|hd\\-(m|p|t)|hei\\-|hi(pt|ta)|hp( i|ip)|hs\\-c|ht(c(\\-|
_|a|g|p|s|t)|tp)|hu(aw|tc)|i\\-(20|go|ma)|i230|iac( |\\-
|\\\/)|ibro|idea|ig01|ikom|im1k|inno|ipaq|iris|ja(t|v)a|jbro|jemu|jigs|kddi|keji|kgt(
|\\\/)|klon|kpt |kwc\\-|kyo(c|k)|le(no|xi)|lg( g|\\\/(k|l|u)|50|54|e\\-|e\\\/|\\-|a-
w)|libw|lynx|m1\\-w|m3ga|m50\\\/|ma(te|ui|xo)|mc(01|21|ca)|m\\-
cr|me(di|rc|ri)|mi(o8|oa|ts)|mmef|mo(01|02|bi|de|do|t(\\-| |o|v)|zz)|mt(50|p1|v
)|mwbp|mywa|n10[0-2]|n20[2-3]|n30(0|2)|n50(0|2|5)|n7(0(0|1)|10)|ne((c|m)\\-
|on|tf|wf|wg|wt)|nok(6|i)|nzph|o2im|op(ti|wv)|oran|owg1|p800|pan(a|d|t)|pdxg|pg(13|\\-([1-
8]|c))|phil|pire|pl(ay|uc)|pn\\-2|po(ck|rt|se)|prox|psio|pt\\-g|qa\\-a|qc(07|12|21|32|60|\\-
[2-7]|i\\-)|qtek|r380|r600|raks|rim9|ro(ve|zo)|s55\\\/|sa(ge|ma|mm|ms|ny|va)|sc(01|h\\-|oo|p\\-
)|sdk\\\/|se(c(\\-|0|1)|47|mc|nd|ri)|sgh\\-|shar|sie(\\-|m)|sk\\-
0|sl(45|id)|sm(al|ar|b3|it|t5)|so(ft|ny)|sp(01|h\\-|v\\-|v
)|sy(01|mb)|t2(18|50)|t6(00|10|18)|ta(gt|lk)|tcl\\-|tdg\\-|tel(i|m)|tim\\-|t\\-
```

```
mo|to(pl|sh)|ts(70|m\|-|m3|m5)|tx\|-9|up(\.b|gl|si)|utst|v400|v750|veri|vi(rg|te)|vk(40|5[0-3]|\|-v)|vm40|voda|vulc|vx(52|53|60|61|70|80|81|83|85|98)|w3c(\|-| )|webc|whit|wi(g|nc|nw)|wmlb|wonu|x700|xda(\|-|2|g)|yas\|-|your|zeto|zte\|-")) {  
%>
```

```
<!DOCTYPE html>
```

```
<html>
```

```
  <head>
```

```
    <meta charset="utf-8">
```

```
    <meta name="viewport" content="width=device-width, minimum-scale=1, maximum-scale=1">
```

```
    <title>mobil login page</title>
```

```
    <link rel="stylesheet" href="http://code.jquery.com/mobile/1.0a4.1/jquery.mobile-1.0a4.1.min.css" />
```

```
    <script type="text/javascript" src="http://code.jquery.com/jquery-1.5.min.js"></script>
```

```
    <script type="text/javascript" src="http://code.jquery.com/mobile/1.0a4.1/jquery.mobile-1.0a4.1.min.js"></script>
```

```
    <style>
```

```
      .errMsg {text-align: center; color: red;}
```

```
    </style>
```

```
  </head>
```

```
  <body>
```

```
    <div data-role="page" data-theme="b" id="editor">
```

```
      <div data-role="header" data-position="inline">
```

```
        <h1>NIIF IdP - mobile login</h1>
```

```
      </div>
```

```
      <div data-role="content">
```

```
        <% if ("true".equals(request.getAttribute("loginFailed"))) { %>
```

```
          <div data-role="fieldcontain">
```

```
            <p class="errMsg">Authentication Failed</p>
```

```
          </div>
```

```
        <% } %>
```

```
        <% if(request.getAttribute("actionUrl") != null){ %>
```

```
          <form action="<%=request.getAttribute("actionUrl")%>"
```

```
method="post" data-ajax="false">
```

```
        <% }else{ %>
```

```
          <form action="j_security_check" method="post">
```

```
        <% } %>
```

```
          <div data-role="fieldcontain">
```

```

        <label for="j_username">Username:</label>
        <input type="text" name="j_username" id="j_username" value=""
/>

    </div>
    <div data-role="fieldcontain">
        <label for="j_password">Password:</label>
        <input type="password" name="j_password" id="j_password"
value="" />
    </div>
    <div data-role="fieldcontain" style="text-align:center">
        <input type="submit" value="Login" data-role="button" data-
inline="true" data-theme="b" />
    </div>
</form>
</div>
</div>
</body>

</html>

<%
} else {

%>

<!DOCTYPE html>
<html>
    <link rel="stylesheet" type="text/css" href="<%= request.getContextPath()%>/login.css"/>
    <head>
        <title>Shibboleth Identity Provider - Example Login Page</title>
    </head>

    <body id="homepage">
        
        <h1>Example Login Page</h1>
        <p>This login page is an example and should be customized. Refer to the
            <a href="https://wiki.shibboleth.net/confluence/display/SHIB2/IdPAuthUserPassLoginPage"
target="_blank"> documentation</a>.
        </p>

        <div class="loginbox">

```

```

<div class="leftpane">
  <div class="content">
    <p>The web site described to the right has asked you to log in and you have chosen
    &lt;FILL IN YOUR SITE&gt; as your home institution.</p>
    <% if ("true".equals(request.getAttribute("loginFailed"))) { %>
      <p><font color="red"> Credentials not recognized. </font> </p>
    <% } %>
    <% if(request.getAttribute("actionUrl") != null){ %>
      <form action="<%=request.getAttribute("actionUrl")%>" method="post">
    <% }else{ %>
      <form action="j_security_check" method="post">
    <% } %>
    <table>
      <tr><td width="40%"><label for="username">Username:</label></td><td><input
name="j_username" type="text" /></td></tr>
      <tr><td><label for="password">Password:</label></td><td><input name="j_password"
type="password" /></td></tr>
      <tr><td></td><td><button type="submit" value="Login" >Continue</button></td></tr>
    </table></form>
  </div>
</div>
<div class="rightpane">
  <div class="content">
    <div id="spName"><idpui:serviceName/></div>
    <!-- pick the logo. If its between 64 & max width/height display it
      If its too high but OK wide clip by height
      If its too wide clip by width.
      We should not clip by height and width since that skews the image. Too high
an image will just show the top.
    -->
    <idpui:serviceLogo minWidth="64" minHeight="64" maxWidth="350" maxHeight="147"
cssId="splogo">
      <idpui:serviceLogo minWidth="64" minHeight="64" maxWidth="350"
cssId="clippedsplogoY">
        <idpui:serviceLogo minWidth="64" minHeight="64" cssId="clippedsplogoX"/>
      </idpui:serviceLogo>
    </idpui:serviceLogo>
    <div id="spDescription">
      <idpui:serviceDescription>You have asked to login to
<idpui:serviceName/></idpui:serviceDescription>
    </div>
  </div>
</div>

```

```
        </div>
    </div>
</div>
</body>
</html>
<% } %>
```

Változat #1

document-uploader hozta létre 2025-08-07 12:06:45 CEST

document-uploader frissítette 2025-08-07 12:06:45 CEST