Shib2IdpTerracottaConfiguration

Shibboleth 2 Terracotta konfiguráció

Shibboleth 2.1.2 IdP -hez

```
<?xml version="1.0" encoding="UTF-8"?>

<tc:tc-config xmlns:tc="http://www.terracotta.org/config"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://www.terracotta.org/config
http://www.terracotta.org/schema/terracotta-4.xsd">

    <!--
        Terracotta configuration file for Shibboleth.

        Complete documentation on the contents of this file may be found here:
        http://terracotta.org/web/display/docs/Configuration+Guide+and+Reference
    -->

    <tc-properties>
        <!-- server-to-server reconnect -->
        <property name="l2.nha.tcgroupcomm.reconnect.enabled" value="true" />
        <property name="l2.nha.tcgroupcomm.reconnect.timeout" value="15000" />

        <!-- client-to-server reconnect -->
        <property name="l2.l1reconnect.enabled" value="true"/>
        <property name="l2.l1reconnect.timeout.millis" value="15000" />
    </tc-properties>
```

```
<servers>
    <!-- START Terracotta server definitions -->
        <server name="idp1" host="idp1.aai.niif.hu">
                <dso>
                        <persistence>
                                <mode>permanent-store</mode>
                        </persistence>
                </dso>

                <logs>/var/log/terracotta/server/logs</logs>
                <data>/var/lib/terracotta/server/data</data>
                <statistics>/var/lib/terracotta/server/stats</statistics>
        </server>

        <server name="idp2" host="idp2.aai.niif.hu">
                <dso>
                        <persistence>
                                <mode>permanent-store</mode>
                        </persistence>
                </dso>

                <logs>/var/log/terracotta/server/logs</logs>
                <data>/var/lib/terracotta/server/data</data>
                <statistics>/var/lib/terracotta/server/stats</statistics>
        </server>

    <!-- END Terracotta server definitions -->

    <ha>
        <mode>networked-active-passive</mode>
        <networked-active-passive>
            <election-time></election-time>
        </networked-active-passive>
    </ha>
</servers>

<system>
    <configuration-model>production</configuration-model>
</system>
```

```
    <clients>
        <logs>/var/log/terracotta/client/logs-%i</logs>
        <statistics>/var/lib/terracotta/client/stats-%i</statistics>
        <modules>
            <module name="tim-vector" version="2.3.1" group-id="org.terracotta.modules"/>
        </modules>
    </clients>
    <application>
        <dso>
            <additional-boot-jar-classes>
                <include>javax.security.auth.Subject</include>
                <include>javax.security.auth.Subject$SecureSet</include>
                <include>javax.security.auth.x500.X500Principal</include>
                <include>javax.security.auth.kerberos.KerberosPrincipal</include>
            </additional-boot-jar-classes>
            <roots>
                <root>
                    <root-name>storageService</root-name>
                    <field-
name>edu.internet2.middleware.shibboleth.common.util.EventingMapBasedStorageService.store</fie
ld-name>
                </root>
            </roots>
            <instrumented-classes>
                <include>
                    <class-expression>edu.vt.middleware.ldap.jaas.LdapPrincipal</class-
expression>
                    <honor-transient>true</honor-transient>
                </include>
                <include>
                    <class-
expression>edu.internet2.middleware.shibboleth.idp.authn.UsernamePrincipal</class-expression>
                    <honor-transient>true</honor-transient>
                </include>
                <include>
                    <class-expression>edu.vt.middleware.ldap.jaas.LdapCredential</class-
expression>
                    <honor-transient>true</honor-transient>
                </include>
                <include>
                    <class-
```

```
expression>edu.internet2.middleware.shibboleth.idp.authn.AuthenticationException</class-
expression>
                    <honor-transient>true</honor-transient>
                </include>
                <include>
                    <class-expression>org.opensaml.util.storage.AbstractExpiringObject</class-
expression>
                    <honor-transient>true</honor-transient>
                </include>
                <include>
                    <class-
expression>edu.internet2.middleware.shibboleth.common.attribute.resolver.provider.attributeDef
inition.TransientIdEntry</class-expression>
                    <honor-transient>true</honor-transient>
                </include>
                <include>
                    <class-
expression>edu.internet2.middleware.shibboleth.idp.authn.LoginContextEntry</class-expression>
                    <honor-transient>true</honor-transient>
                </include>
                <include>
                    <class-
expression>edu.internet2.middleware.shibboleth.idp.authn.LoginContext</class-expression>
                    <honor-transient>true</honor-transient>
                </include>
                <include>
                    <class-
expression>edu.internet2.middleware.shibboleth.idp.authn.ShibbolethSSOLoginContext</class-
expression>
                    <honor-transient>true</honor-transient>
                </include>
                <include>
                    <class-
expression>edu.internet2.middleware.shibboleth.idp.authn.Saml2LoginContext</class-expression>
                    <honor-transient>true</honor-transient>
                </include>
                <include>
                    <class-
expression>edu.internet2.middleware.shibboleth.idp.session.impl.AuthenticationMethodInformatio
nImpl</class-expression>
                    <honor-transient>true</honor-transient>
```

```
                </include>
                <include>
                    <class-expression>org.opensaml.util.storage.ReplayCacheEntry</class-
expression>
                    <honor-transient>true</honor-transient>
                </include>
                <include>
                    <class-
expression>edu.internet2.middleware.shibboleth.idp.session.impl.SessionManagerEntry</class-
expression>
                    <honor-transient>true</honor-transient>
                </include>
                <include>
                    <class-
expression>edu.internet2.middleware.shibboleth.common.session.impl.AbstractSession</class-
expression>
                    <honor-transient>true</honor-transient>
                </include>
                <include>
                    <class-
expression>edu.internet2.middleware.shibboleth.idp.session.impl.SessionImpl</class-expression>
                    <honor-transient>true</honor-transient>
                </include>
                <include>
                    <class-
expression>edu.internet2.middleware.shibboleth.idp.session.impl.ServiceInformationImpl</class-
expression>
                    <honor-transient>true</honor-transient>
                </include>
                <include>
                    <class-
expression>org.opensaml.common.binding.artifact.BasicSAMLArtifactMapEntry</class-expression>
                    <honor-transient>true</honor-transient>
                </include>
                <include>
                   <class-expression>org.opensaml.xml.util.LazyList</class-expression>
                   <honor-transient>true</honor-transient>
               </include>
            </instrumented-classes>
            <locks>
                <autolock auto-synchronized="false">
```

```
                    <method-expression>*
edu.vt.middleware.ldap.jaas.LdapPrincipal.*(..)</method-expression>
                    <lock-level>write</lock-level>
                </autolock>
                <autolock auto-synchronized="false">
                    <method-expression>*
edu.internet2.middleware.shibboleth.idp.authn.LoginContext.set*(..)</method-expression>
                    <lock-level>write</lock-level>
                </autolock>
                <autolock auto-synchronized="false">
                    <method-expression>*
edu.internet2.middleware.shibboleth.idp.authn.LoginContext.get*(..)</method-expression>
                    <lock-level>read</lock-level>
                </autolock>
                <autolock auto-synchronized="false">
                    <method-expression>*
edu.internet2.middleware.shibboleth.idp.authn.ShibbolethSSOLoginContext.set*(..)</method-
expression>
                    <lock-level>write</lock-level>
                </autolock>
                <autolock auto-synchronized="false">
                    <method-expression>*
edu.internet2.middleware.shibboleth.idp.authn.ShibbolethSSOLoginContext.get*(..)</method-
expression>
                    <lock-level>read</lock-level>
                </autolock>
                <autolock auto-synchronized="false">
                    <method-expression>*
edu.internet2.middleware.shibboleth.idp.authn.Saml2LoginContext.set*(..)</method-expression>
                    <lock-level>write</lock-level>
                </autolock>
                <autolock auto-synchronized="false">
                    <method-expression>*
edu.internet2.middleware.shibboleth.idp.authn.Saml2LoginContext.get*(..)</method-expression>
                    <lock-level>read</lock-level>
                </autolock>
                <autolock auto-synchronized="false">
                    <method-expression>*
edu.internet2.middleware.shibboleth.common.session.impl.AbstractSession.set*(..)</method-
expression>
                    <lock-level>write</lock-level>
```

```
                </autolock>
                <autolock auto-synchronized="false">
                    <method-expression>*
edu.internet2.middleware.shibboleth.common.session.impl.AbstractSession.get*(..)</method-
expression>
                    <lock-level>read</lock-level>
                </autolock>
                <autolock auto-synchronized="false">
                    <method-expression>*
edu.internet2.middleware.shibboleth.idp.session.impl.SessionImpl.set*(..)</method-expression>
                    <lock-level>write</lock-level>
                </autolock>
                <autolock auto-synchronized="false">
                    <method-expression>*
edu.internet2.middleware.shibboleth.idp.session.impl.SessionImpl.get*(..)</method-expression>
                    <lock-level>read</lock-level>
                </autolock>
                <autolock auto-synchronized="false">
                    <method-expression>*
edu.internet2.middleware.shibboleth.idp.session.impl.AuthenticationMethodInformationImpl.set*(
..)</method-expression>
                    <lock-level>write</lock-level>
                </autolock>
                <autolock auto-synchronized="false">
                    <method-expression>*
edu.internet2.middleware.shibboleth.idp.session.impl.AuthenticationMethodInformationImpl.get*(
..)</method-expression>
                    <lock-level>read</lock-level>
                </autolock>
                <autolock auto-synchronized="false">
                    <method-expression>*
edu.internet2.middleware.shibboleth.idp.session.impl.ServiceInformationImpl.set*(..)</method-
expression>
                    <lock-level>write</lock-level>
                </autolock>
                <autolock auto-synchronized="false">
                    <method-expression>*
edu.internet2.middleware.shibboleth.idp.session.impl.ServiceInformationImpl.get*(..)</method-
expression>
                    <lock-level>read</lock-level>
                </autolock>
```

```
            </locks>
        </dso>
    </application>
</tc:tc-config>
```

Változat #1
cziernorbert hozta létre 2026-04-14 13:22:49 CEST
cziernorbert frissítette 2026-04-17 10:56:22 CEST